

SAFETY DATA SHEET



CHESSER CHEMICALS Pty Ltd 124 Days Rd FERRYDEN PARK South Australia 5010 Australia Telephone +61 8 8406 0000 Facsimile +61 8 8406 0099 Email reception@chesserchemicals.com.au ABN Number: 67 008 262 039

Disclaimer

CHESSER CHEMICALS Pty Ltd provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.

Product: EXTRA KLEEN HD

HAZARDOUS according to the criteria of the Globally Harmonised System of Classification and Labelling of Chemicals

DANGER SIGNAL WORD:



Emergency Response No: CHEMWATCH

1800 951 288

RECOMMENDED PPE





Hazards

H290 May be corrosive to metals

H314 Causes severe skin burns and eye damage.



SAFFTY DATA SHFFT

Page 2 of 6 Product: **EXTRA KLEEN HD** Issued: January 2024

1 IDENTIFICATION

IDENTIFICATION

Product Code: EXK

Product Name: EXTRA KLEEN HD Other Names: Not applicable

Product Use: Caustic based Hard Surface Cleaner

Restrictions on use: Use according to Directions; avoid contact with acids. Use

appropriate PPE.

COMPANY DETAILS

Company: CHESSER CHEMICALS Pty Ltd

ABN Number: 67 008 262 039 Address: 124 Days Road

FERRYDEN PARK SA 5010

Telephone Number: (08) 8406 0000 Facsimile Number: (08) 8406 0099

Emergency Telephone Number: CHEMWATCH 1800 951 288

Other Information: This information summarises our best knowledge on the health and safety

hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace

including in conjunction with other products.

2 HAZARD IDENTIFICATION

HAZARDOUS SUBSTANCE DANGEROUS GOODS

according to criteria of Safe Work Australia

as classified by the criteria of the Australian Dangerous Goods

Code (ADG Code) for Transport by Road and Rail.

Classification of the substance or mixture:

Corrosive to Metals - Category 1
Skin Corrosion - Category 1
Eye Damage - Category 1

SIGNALWORD:

DANGER



Corrosion

Hazard Statements

Physical hazards

H290 May be corrosive to metals.

Health hazards

H314 Causes severe skin burns and eye damage.

Environmental hazards

H402 Harmful to aquatic life

Other Hazards
Not Listed

Precautionary statements

General precautionary statements Prevention precautionary statements

P260 Do not breathe mist/vapours/spray.
P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P234 Keep only in original container.

Response precautionary statements





SAFFTY DATA SHFFT

Product: **EXTRA KLEEN HD**Issued: January 2024

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P363 Wash contaminated clothing before re-use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable

for breathing.

P310 Immediately call a POISON CENTRE or doctor/physician.
P321 Specific treatment (see First Aid Measures on Safety Data

Sheet).

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

P390 Absorb spillage to prevent material damage.

Storage precautionary statements

P405 Store locked up.

P406 Store in corrosive resistant container.

Disposal precautionary statements

P501 Dispose of contents/container in accordance with

local/regional/national/international regulations.

Poisons Schedule (SUSMP): S6 Poison.

3 COMPOSITION

Ingredients

Chemical EntityCAS NumberProportionRisk PhrasesPOTASSIUM HYDROXIDE[1310-58-3]1 - 10%H290 H314 H318Disodium metasilicate[10213-79-3]1 - 10%H314 H318

Water [7732-18-5] > 60% Ingredients determined not to be hazardous Balance

4 FIRST AID MEASURES

Ingestion: If swallowed do NOT induce vomiting. Immediately wash out mouth with water. Seek urgent

medical attention.

Eye: If in eyes, hold eye lids apart and flush eye continuously with running water. Continue flushing

until advised to stop by the Poisons Information centre or a doctor, or for at least 15 minutes.

Seek urgent medical attention.

Skin: If skin contact occurs, remove contaminated clothing and flush skin and hair with running

water. Do not re-use contaminated clothing until washed. Seek medical attention.

Inhaled: Remove from contaminated area to fresh air. If problem persists seek urgent medical attention

First Aid Facilities Eye wash and safety shower

Advice to Doctor Treat symptomatically, Can cause severe eye damage.

5 FIRE FIGHTING MEASURES

Fire Extinguishing Media: Use appropriate extinguishing media to suit surrounding

area

Hazards from Combustion: Material does not burn

Precaution for Fire Fighters: Wear chemical splash suit and SCBA

Corrosive liquid. Contact with metals may evolve flammable hydrogen gas

Hazchem 2F

6 ACCIDENTAL RELEASE MEASURES

Emergency Procedures Keep unauthorised people away. Do not touch or walk through spilled

material. Do not touch damaged containers or spilled material unless

wearing appropriate protective clothing

Clean Up Spills will be slippery so treat promptly. For minor spills mop up and rinse

with water. For larger spills absorb material on mineral absorbent material or absorbent pads. Collect and put into plastic bags and dispose of through

waste disposal contractor. Rinse area with water.



SAFFTY DATA SHFFT

Page 4 of 6 Product: EXTRA KLEEN HD Issued: January 2024

7 HANDLING AND STORAGE

Handling Wear appropriate protective clothing to prevent skin and eye contact. Use in well ventilated

area. Keep containers closed when not in use. Maintain a high standard of personal hygiene.

Wash hands immediately after using product

Corrosive product. Store in cool, dry, well ventilated place out of direct sunlight. Store in **Storage**

closed containers. Store away from incompatible materials such as acids, aluminium and

zinc. Ensure storage area is secure

8 EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure Standards None listed for product.

Engineering Controls EXTRA KLEEN HD can be used manually or through a foamer. Use in well

ventilated area and maintain levels below exposure standards.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.





CHEMICAL GOGGLES or SAFETY GLASSES **IMPERVIOUS GLOVES**

Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If risk of inhalation exists, wear suitable mist respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear colourless foaming liquid.

Odour Neutral **Boiling Point:** >100°C **Specific Gravity:** 1.13 Flash Point: N/A Flammability Limits: N/A Solubility in Water: Soluble

Other Properties

> 13.0 pH (neat)

10 STABILITY AND REACTIVITY

Stability Stable under normal conditions of use and storage.

Hazardous Decomposition Products: No special requirements.

Hazardous Polymerization: Will not occur.

Incompatibilities: Acids, aluminium, zinc, brass and painted surfaces.

Conditions to Avoid: Reacts violently with acids. Attacks aluminium, tin and zinc

11 TOXICOLOGICAL INFORMATION

Ingestion Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and bleeding. Can

cause chemical burns to the mouth, oesophagus and gastrointestinal tract

Eye Corrosive to eyes. Will cause severe irritation and chemical burns. Contamination of eyes

can result in permanent injury or blindness

Skin Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns

Inhalation Mist generated may cause severe irritation to the mucous membranes and upper

respiratory tract

Chronic Effects Prolonged or repeated exposure to this product will result in skin irritation and possibly

result in dermatitis

Toxicological Data Non available for EXTRA KLEEN HD.

12 ECOLOGICAL INFORMATION

Ecotoxicity: No information found. Avoid contaminating waterways.



Issued: January 2024



SAFFTY DATA SHFFT

13 DISPOSAL CONSIDERATIONS

Refer to Waste Management Authority. Dispose of material through licensed waste contractor. Assure conformity with all applicable regulations.

14 TRANSPORT INFORMATION

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for

Transport by Road and Rail; DANGEROUS GOODS.

UN No: **Transport Hazard Class:** 8 Corrosive

Contains Potassium hydroxide

Packing Group: Ш

Proper Shipping Name: Caustic Alkali Liquid N.O.S.

Hazchem or Emergency Action Code:

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG

Code) for transport by sea; DANGEROUS GOODS.

UN No: 1719 **Transport Hazard Class:** 8 Corrosive

Contains Potassium hydroxide

Packing Group:

Proper Shipping Name or Technical Name: Caustic Alkali Liquid N.O.S.

IMDG EMS Fire: F-A IMDG EMS Spill: S-B

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA)

Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1719 8 Corrosive **Transport Hazard Class:**

Contains Potassium hydroxide

Packing Group:

Proper Shipping Name or Technical Name: Caustic Alkali Liquid N.O.S.

15 REGULATORY INFORMATION

Poisons Schedule S6 EPG 8A1

AICS Name All the constituents of this material are listed on Inventory.

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS SUBSTANCE.

Classification of the substance or mixture:

Corrosive to Metals - Category 1 Skin Corrosion - Category 1 Eye Damage - Category 1

Hazard Statement(s):

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

16 OTHER INFORMATION

Literature References No data available. **Sources for Data** No data available.

Legend to Abbreviations and Acronyms

< less than G gram greater than g/cm³ grams per cubic centimetre **AICS**

Australian Chemical grams per litre Inventory g/l Substances **HSNO** Hazardous Substance and

CAS Chemical Abstracts Service (Registry Organism

IDLH Immediately Dangerous to Life and Number) cm²

square centimetres Health

CO₂ Carbon Dioxide **Immiscible** liquids are insoluble in each other

COD Chemical Oxygen Demand Kg kilogram

kg/m³ deg C (°C) degrees Celsius kilograms per cubic metre **ERMA**

Environmental Risk Management LC50 LC stands for lethal concentration. Authority LC50 is the concentration of a



SAFETY DATA SHEET

Page 6 of 6 Product: EXTRA KLEEN HD Issued: January 2024

material in air which causes the death a set period of time, usually 1 or 4 hours.

Not Applicable

Threshold Limit Value

of 50% (one half) of a group of test

animals. The material is inhaled over

LD50 LD stands for Lethal Dose, LD50 is **NOHSC** National Occupational Health and

the amount of a material, given all at Safety Commission **OECD** once, which causes the death of 50% Organization for Economic Co-

operation and Development (one half) of a group of test animals

TLV

N/A

Ltr **PEL** Permissible Exposure Limit cubic metre m^3

parts per billion ppb mbar millibar parts per million ppm milligram ppm/2h

parts per million per 2 hours mg mg/24H milligrams per 24 hours parts per million per 6 hours ppm/6h **RCP** milligrams per kilogram Reciprocal Calculation Procedure mg/kg mg/m³ milligrams per cubic metre **STEL** Short Term Exposure Limit

Miscible liquids form one homogeneous liquid tonne tne

phase regardless of the amount of Time Weighted Average **TWA** either component present ug/24H micrograms per 24 hours United Nations (number) millimetre UN

mPa.s milli Pascal per second Wt weight

Date Prepared:

miscible

Misc

mm

Supersedes: Monday 25th March 2019 Tuesday 16th January 2024 Version: 1.1

Update date

CHESSER CHEMICALS Pty Ltd Telephone: (08) 8406 0000 124 Days Road Facsimile: (08) 8406 0099

FERRYDEN PARK SA 5010 reception@chesserchemicals.com.au e-Mail: