



CHESSER CHEMICALS Pty Ltd
124 Days Rd FERRYDEN PARK
South Australia 5010 Australia
Telephone +61 8 8406 0000
Facsimile +61 8 8406 0099
Email reception@chesserchemicals.com.au
ABN Number: 67 008 262 039

Disclaimer:

CHESSER CHEMICALS Pty Ltd provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.

Product: **GRILL POWER**

HAZARDOUS according to the criteria of the Globally Harmonised System of Classification and Labelling of Chemicals

SIGNAL WORD: **DANGER**



 Emergency Response No: 1800 951 288

RECOMMENDED PPE



Hazards

H290

May be corrosive to metals

H302

Harmful if swallowed.

H314

Causes severe skin burns and eye damage.

**1 IDENTIFICATION****IDENTIFICATION**

Product Code: GRP
 Product Name: GRILL POWER
 Other Names: Not applicable
 Product Use: Caustic based Hard Surface Cleaner
 Restrictions on use: Use according to Directions; Use appropriate PPE. Protect skin and eyes

COMPANY DETAILS

Company: CHESSER CHEMICALS Pty Ltd
 ABN Number: 67 008 262 039
 Address: 124 Days Road
 FERRYDEN PARK SA 5010
 Telephone Number: (08) 8406 0000
 Facsimile Number: (08) 8406 0099
 Emergency Telephone Number: CHEMWATCH 1800 951 288

Other Information: This information summarises our best knowledge on the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products.

2 HAZARD IDENTIFICATION

HAZARDOUS according to the criteria of the Globally Harmonised System of Classification and Labelling of Chemicals

Classification of the substance or mixture:

Acute Toxicity - Category 4
 Skin Corrosion - Category 1B
 Eye Damage - Category 1
 Corrosive to metals - Category 1

SIGNALWORD:**DANGER**

Exclamation Mark



Corrosion

Hazard Statements**Physical hazards**

H290 May be corrosive to metals.

Health hazards

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

Environmental hazards

H402 Harmful to aquatic life

Other Hazards

Not Listed

Precautionary statements**General precautionary statements**

P102 Keep out of reach of children

Prevention precautionary statements

P234 Keep only in original container

P264 Wash hands thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P260 Do not breathe mists or sprays

P280 Wear protective gloves and eye protection.

P390 Absorb spillage to prevent material damage

**Response precautionary statements**

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.
P363	Wash contaminated clothing before reuse.
P310	Immediately call Poisons Information Centre or a doctor.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P321	Additional information is listed in the Safety Data Sheet.

Storage precautionary statements

P405	Store locked up.
P406	Store in corrosive resistant container with a resistant inner liner.

Disposal precautionary statements

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Poisons Schedule (SUSMP): S6 Poison.**3 COMPOSITION****Ingredients**

Chemical Entity	CAS Number	Proportion	Risk Phrases
POTASSIUM HYDROXIDE	[1310-58-3]	10 - 30%	H290 H314 H318
Propylene glycol mono-methyl ether	[107-98-2]	1 – 10%	
Water	[7732-18-5]	> 50%	
Ingredients determined not to be hazardous		Balance	

4 FIRST AID MEASURES

Ingestion:	If swallowed do NOT induce vomiting. Immediately wash out mouth with water. Seek urgent medical attention.
Eye:	If in eyes, hold eye lids apart and flush eye continuously with running water. Continue flushing until advised to stop by the Poisons Information centre or a doctor, or for at least 15 minutes. Seek urgent medical attention.
Skin:	If skin contact occurs, remove contaminated clothing and flush skin and hair with running water. Do not re-use contaminated clothing until washed. Seek medical attention.
Inhaled:	Remove from contaminated area to fresh air. If problem persists seek urgent medical attention
First Aid Facilities	Eye wash and safety shower
Advice to Doctor	Treat symptomatically, Can cause severe eye damage.

5 FIRE FIGHTING MEASURES

Fire Extinguishing Media:	Use appropriate extinguishing media to suit surrounding area
Hazards from Combustion:	Material does not burn
Precaution for Fire Fighters:	Wear chemical splash suit and SCBA
Corrosive liquid.	Contact with metals may evolve flammable hydrogen gas
Hazchem	2R

6 ACCIDENTAL RELEASE MEASURES

Emergency Procedures	Keep unauthorised people away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing
Clean Up	Spills will be slippery so treat promptly. For minor spills mop up and rinse with water. For larger spills absorb material on mineral absorbent material or absorbent pads. Collect and put into plastic bags and dispose of through waste disposal contractor. Rinse area with water.

7 HANDLING AND STORAGE

Handling	Wear appropriate protective clothing to prevent skin and eye contact. Use in well ventilated area. Keep containers closed when not in use. Maintain a high standard of personal hygiene. Wash hands immediately after using product
-----------------	---



Storage Corrosive product. Store in cool, dry, well ventilated place out of direct sunlight. Store in closed containers. Store away from incompatible materials such as acids, aluminium and zinc. Ensure storage area is secure

8 EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure Standards None listed for product.
Engineering Controls Do not inhale vapours. Use in well ventilated area and maintain levels below exposure standards.
Personal Protective Equipment Wear chemical goggles or safety glasses and impervious gloves when using product. If sprayed through a high pressure sprayer wear full chemical suit and approved respirator or air supply in accordance with AS/NZS 1715/1716

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

RECOMENDED



CHEMICAL GOGGLES or SAFETY GLASSES
IMPERVIOUS GLOVES

Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If risk of inhalation exists, wear suitable mist respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear viscous liquid.
Odour Neutral
Boiling Point: >100°C
Specific Gravity: 1.20
Flash Point: N/A
Flammability Limits: N/A
Solubility in Water: Soluble
Other Properties
pH (neat) > 13.0

10 STABILITY AND REACTIVITY

Stability Stable under normal conditions of use and storage.
Hazardous Decomposition Products: May evolve toxic gases when heated to decomposition.
Hazardous Polymerization: Will not occur.
Incompatibilities: Incompatible with acids, oxidising agents (i.e. peroxides), active metals and heat and ignition sources.
Conditions to Avoid: Incompatible with acids, oxidising agents (i.e. peroxides), active metals and heat and ignition sources.

11 TOXICOLOGICAL INFORMATION

Ingestion Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and bleeding. Can cause chemical burns to the mouth, oesophagus and gastrointestinal tract
Eye Corrosive to eyes. Will cause severe irritation and chemical burns. Contamination of eyes can result in permanent injury or blindness
Skin Contact with skin will result in severe irritation. Corrosive to skin – may cause skin burns
Inhalation Mist generated may cause severe irritation to the mucous membranes and upper respiratory tract
Toxicological Data Non available for Grill POWER.

12 ECOLOGICAL INFORMATION

Ecotoxicity: No information found. Avoid contaminating waterways.

13 DISPOSAL CONSIDERATIONS

Refer to Waste Management Authority. Dispose of material through licensed waste contractor. Assure conformity with all applicable regulations.



14 TRANSPORT INFORMATION

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

UN No: 1719
 Transport Hazard Class: 8 Corrosive
 Packing Group: II
 Proper Shipping Name: Caustic Alkali Liquid N.O.S.
 Hazchem or Emergency Action Code: 2R



Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No: 1719
 Transport Hazard Class: 8 Corrosive
 Packing Group: II
 Proper Shipping Name or Technical Name: Caustic Alkali Liquid N.O.S.
 IMDG EMS Fire: F-A
 IMDG EMS Spill: S-B



Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1719
 Transport Hazard Class: 8 Corrosive
 Packing Group: II
 Proper Shipping Name or Technical Name: Caustic Alkali Liquid N.O.S.



15 REGULATORY INFORMATION

Poisons Schedule S6
 EPG 8A1
 AICS Name All the constituents are listed on Inventory

16 OTHER INFORMATION

Literature References No data available.

Sources for Data No data available.

Legend to Abbreviations and Acronyms

< less than
 > greater than
 AICS Australian Inventory of Chemical Substances
 CAS Chemical Abstracts Service (Registry Number)
 cm² square centimetres
 CO₂ Carbon Dioxide
 COD Chemical Oxygen Demand
 deg C (°C) degrees Celsius
 ERMA Environmental Risk Management Authority
 G gram
 g/cm³ grams per cubic centimetre
 g/l grams per litre
 LD50 LD stands for Lethal Dose. LD50 is the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals
 Ltr Litre
 m³ cubic metre
 mbar millibar
 mg milligram
 mg/24H milligrams per 24 hours
 mg/kg milligrams per kilogram
 mg/m³ milligrams per cubic metre
 Misc miscible

HSNO Hazardous Substance and New Organism
 IDLH Immediately Dangerous to Life and Health
 Immiscible liquids are insoluble in each other
 Kg kilogram
 kg/m³ kilograms per cubic metre
 LC50 LC stands for lethal concentration. LC50 is the concentration of a material in air which causes the death of 50% (one half) of a group of test animals. The material is inhaled over a set period of time, usually 1 or 4 hours.
 Miscible liquids form one homogeneous liquid phase regardless of the amount of either component present
 mm millimetre
 mPa.s milli Pascal per second
 N/A Not Applicable
 NOHSC National Occupational Health and Safety Commission
 OECD Organization for Economic Co-operation and Development
 PEL Permissible Exposure Limit
 ppb parts per billion
 ppm parts per million
 ppm/2h parts per million per 2 hours
 ppm/6h parts per million per 6 hours



SAFETY DATA SHEET

Page 6 of 6
Product: **GRILL POWER**
Issued: January 2024

CHESSERCHEMICALS

RCP Reciprocal Calculation Procedure
STEL Short Term Exposure Limit
TLV Threshold Limit Value
tne tonne

TWA
ug/24H
UN
Wt

Time Weighted Average
micrograms per 24 hours
United Nations (number)
weight

Date Prepared:

Monday 15th January 2024

Version: 1.2

Supersedes:

Friday 29th March 2019

Update Date



CHESSER CHEMICALS Pty Ltd
124 Days Road
FERRYDEN PARK SA 5010

Telephone: (08) 8406 0000

Facsimile: (08) 8406 0099

e-Mail: reception@chesserchemicals.com.au